


DATASHEET

Thermal Protector N02

Type series 02



Construction and function

The switchgear of type series 02 is fixed in a positive lock and is self-aligning between the floor of a conductive housing (1) and a contact cap which is made of steel (2) and insulated from it, plus an integrated stationary silver contact (6) which closes the housing like a button cell. By means of a throw force a bimetallic disc (5) pushes the movable contact (4) that sticks out in the middle of it onto its circumferential collar (6) against the spring snap-in disc (3) that is also surrounding the contact (4). Due to the higher throw force of the bimetallic disc (5) the switch contact remains open against the mechanical resistance of the spring snap-in disc (3) before reaching the rated switching temperature. As such, the contact also remains open as long as the bimetallic disc – only reacting to the ambient temperature – continually works and its shape changes. The bimetallic disc (5) only snaps into its inverted position when the rated switching temperature is reached and the contact is closed by the abruptly released pressure of the spring snap-in disc (3). The spring snap-in disc (3) is now a transfer element for electric current and as such, it enables the bimetallic disc (5) to continue to work on a continuous basis. When the reset temperature is reached, the bimetallic disc snaps back into its start position and the contact is opened again.



Features:

Specially flat design	to fit closely built-up circuits
Quick response sensitivity	Featured by small protector mass and the metal-housing
Excellent long term performance	due to instantaneous switching, fine silver contacts, constant contact resistance and to electrically as well as mechanically unstressed bimetallic disc, reproducible switching temperature values
Instantaneous switching	always with the same contact pressure up to reset point; resulting in low contact stress
Very short bounce times	< 1 ms
Temperature resistance	by use of high temperature resistant materials and components



N02

Type: Normally open; resets automatically; with a connection wire; partially insulated in a plastic cap




Installation height h	from 3,4 mm
Diameter d	10,0 mm
Length of the connection pins	14,0 mm / 20,0 mm

Nominal switching temperature (NST) in 5 °C increments		60 °C - 200 °C
Tolerance (standard)		±5 K
Reverse Switch Temperature (defined RST is possible at the customer's request)	UL	≥ 35 °C (≤ 80 °C NST) -35 K ± 15 K (≥ 85 °C ≤ 180 °C NST)
	VDE	-65 K ± 15 K (≥ 185 °C ≤ 200 °C NST) ≥ 35 °C
Installation height		from 3,4 mm
Diameter		10,0 mm
Length of the connection pins		14,0 mm / 20,0 mm
Resistance to impregnation *		suitable
Suitable for installation in protection class		I
Pressure resistance to the switch housing *		450 N
Standard connection		Connecting wire with d = 0,5 mm
Available approvals (please state)		IEC; ENEC; VDE; CSA; CQC
Operating voltage range AC		up until 500 V AC
Rated voltage AC		250 V (VDE) 277 V (UL)
Rated current AC cos φ = 1.0/cycles		2,5 A / 10.000
Rated current AC cos φ = 0.6/cycles		1,6 A / 10.000
Total bounce time		< 1 ms
Contact resistance (according to MIL-STD. R5757)		≤ 50 mΩ
Vibration resistance at 10 ... 60 Hz		100 m/s ²

* In accordance with the Thermik test - Specifications relating to the application (on the part of the buyer) which details from our standards are not checked for their correctness in respect of application and/or conformity with standards. The responsibility for respect of the suitability of Thermik products for each application falls on the user. - Slight deviations are considered in terms of dimensions and values, depending on the embodiment of the product. - We reserve the right to make technical changes in the course of further development. - Details concerning certain data, measurement methods, applications, approvals, etc., can be supplied upon request.

Ordering example:



Marking example:



More varieties of the type series 02:

- C02 – with connector cables; with or without epoxy; without insulation
- S02 –with connector cables; with or without epoxy; insulation: Mylar®-Nomex®
- L02 – with connector cables; with epoxy; fully insulated in a screw on housing
- C02 Pin – with pins; with epoxy; without insulation

- www.thermik.de/data/C02
- www.thermik.de/data/S02
- www.thermik.de/data/L02
- www.thermik.de/data/C02-Pin